MISSION CRITICAL PRINTING SOLUTION

INDUSTRIAL. RUGGED. VERSATILE.



JE FIL

01

DIGITAL COLOR PRINTER 11" × 17"/A3

www.printronix.com



## Mission-critical printing for industries that rely on speed and efficiency.

### The Printronix LP844C gets the job done, enabling you to get on with yours.

Affordable, versatile, and built to deliver high-quality results, the LP844C provides professional tabloid/A3-sized high definition color output at speeds that meet the demands of your business.

With media handling capabilities that are unmatched in its class, the LP844C adapts to the specific needs of your business. Multiple paper trays allow for expansive paper handling capabilities, fitting up to 2,540 sheets, and easily handles substrates with weights between 64 and 256gsm. This gives users endless production abilities in-house, on demand.

The versatility and straight-through paper path make it effortless for users to run ultra-thick sheets for labels in one moment and print full color customer-facing documents the next, making it the most powerful compact-sized industrial printers in the market.

The LP844C is a game-changer for businesses, consistently delivering high performance results for the most demanding industrial environments. And with its unique tabloid/A3 media capabilities and world-class service and support from Printronix, users can increase uptime and enable continuous movement in business-critical situations.





# Built for your

When users require speed and efficiency, the LP844C is there to get the job done. It's designed to work as hard as you do, providing years of reliable performance.

- Freight and logistics
- Shipping/receiving
- Warehouse/fulfillment
- Order picking/packing
- Inventory management
  - Product labeling
- Retail and storefront
- Invoicing/receipts
- Service documentation
- Safety and compliance materials
- Healthcare/medical

## Why choose the LP844C?

Your business deserves a powerful device that seamlessly integrates with daily operations, and the Printronix LP844C packs loads of production enhancing functions that help get the job done. Built with industrial operations in mind, it provides remarkably reliable performance, increases productivity, and ultimately improves workflow efficiency.

- Smallest Tabloid/A3 printer in the market It's ultracompact design, advanced features, and expansive print capabilities make it one of the most powerful Tabloid/A3-sized (11" x 17") printers in the market
- Unrivaled TCO The LP844C is designed to print, and print, and print. Its long life and high duty cycle are supported with separate toners and drums to ensure the maximum usage of all consumables.
- Most versatile media handling capabilities High-capacity paper trays fit up to 2,540 sheets and easily handles media between 64 and 256gsm, in sizes up to 11" x 17" (Tabloid/A3) and 52" (1.32m) long
- Indoor/outdoor substrate durability Print magnetic and ultra-durable water/tear proof materials suitable for both indoor and outdoor applications. Perfect for warehouse and production environments, shelf labeling, and signage.
- Superior print speeds Time matters and the LP844C is ready to meet those demands, printing up to 36 color ppm, with ease
- Full HD color capabilities Print 1200 x 1200 dpi images in high-definition color - perfect for customer-facing documents
- Adaptability The world is changing, and the LP844C can be configured to meet the unique needs of your industrial environment.
- World-class service and support Printronix has been addressing global customer needs for mission-critical printing for more than 45 years, delivering customized solutions and services to support and improve uptime in industrial environments.



 Mobile connectivity – Wireless, tap and print NFC functionality, as well as AirPrint and Android-ready



## **LP844C Product Specifications**

#### **PRINT SPEED**

Print speed Time to first print Warm up time

36ppm color/mono<sup>1</sup> 6.3 seconds color/mono<sup>1</sup> ≤20 seconds from power on  $\leq$  9.9 seconds from power save

#### **PRINT QUALITY**

Resolution

1200 x 1200 dpi

#### **DUTY CYCLE**

Maximum: Average:

50,000 pages/month; 10,000 pages/month

#### MEMORY

1GB RAM; 3GB eMMC

#### **OPERATION PANEL**

Mono LCD

#### **CONNECTIVITY/INTERFACES**

USB 2.0 Device, USB 2.0 Hostx1, 10 Base-T/100 Base-TX/1000 Base-T Ethernet; NFC<sup>2</sup>, Wireless IEEE802. 11a/b/g/n

#### **PRINTER LANGUAGES**

PCL6 (XL3.0) and PCL5c, Postscript 3 (emulation), SIDM (IBM-PPR, EPSON-FX), PDF (V1.7)

#### **NETWORK & PROTOCOLS**

TCP/IPv4&v6, NetBIOS over TCP, DHCP, DHCPv6, BOOTP, HTTP, HTTPS, DNS, DDNS, WINS, UPNP, Bonjour, SMTP, SMTPS, POP3, POP3S, SNMPv1&v3, SNTP, IPP, IPPS, WSD Print, LLTD, IEEE802.1X, LPR, Port9100, Telnet, FTP, FTPS, IPSec, Secure Protocol Server, LDAP, LDAPS, Google Cloud Print 2.0, AirPrint, WLAN IEEE802.11a/b/g/n, WEP, WPA (Personal Enterprise), WPA2 (Personal Enterprise)

#### **OS COMPATIBILITY**

Windows 7 (32-bit & 64-bit) and higher; Mac OS X 10.10 and higher

#### **ADVANCED NETWORKING & SECURITY**

Color Correct, Printronix LPR<sup>3</sup>, Color Swatch Utility<sup>3</sup>, smart PrintSuperVision<sup>3</sup>, Print Job Accounting Client, Network Card Setup<sup>4</sup>, Configuration Tool<sup>3</sup>, PS Gamma Adjuster, Firmware Update Tool, Profile Assistant<sup>4</sup>, Monitoring Tool<sup>3</sup>, Network Extension<sup>3</sup>

#### **BARCODES & SPECIALTY FONTS**

10 types of one dimension with 26 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET; 2 types of two dimensions: PDF417, JIS-X0510, QR code Mode 2; Printer fonts: Scalable: 87 PCL Fonts and 80 PostScript fonts (emulation); Bitmap fonts: 4 PCL fonts (Lineprinter, OCR-A/B, USPS ZIP Barcode)

#### **CONSUMABLES**

Toner cartridges<sup>5</sup> Image drums<sup>6</sup> Fuser<sup>6</sup> Transfer belt

10,000 pages 30,000 pages 100,000 pages 80,000 pages

- DIGITAL
- <sup>1</sup> Published performance results based on laboratory testing. Individual results may apply.
- <sup>2</sup> For Android only.
- <sup>3</sup> Windows only
- 4 Mac OSX only. 5 Average continuous print page yield in accordance with ISO/
- IEC 19798. Individual results may vary
- 6 Estimated average life, based on 3 pages per job.
- <sup>7</sup> Printer shipped with toner for 2,500 A4 pages.
- <sup>8</sup> Available in the US only

© 2022 Printronix, LLC. All rights reserved. Printronix and all product names, numbers and logos are trademarks or registered trademarks of Printronix, LLC. Product appearance and/or specifications are subject to change without notice. Windows is a registered trademark of Microsoft Corporation in the United States and other countries. All other trademarks, product names and Company names or logos herein, are the property of their respective owners. PTX-30003

#### **ENVIRONMENTAL COMPLIANCE**

ENERGY STAR 3.0 (TEC Value 0.57KWh)

#### **NOISE LEVEL**

Operating 54dBA; Standby 32dBA or less; Power Save Inaudible

#### **DIMENSIONS (WxDxH)**

17.6" x 21.7" x 14.1" (449mm x 552mm x 360mm)

#### WEIGHT

Approx. 88.2 lbs (40 kg) including all consumables<sup>7</sup>

#### WARRANTY

Printer: 1 year onsite next day<sup>8</sup>; LED Printheads: 5 year limited warranty

#### PAPER INPUT CAPACITY

400 sheets of 80gsm Standard (300-sheet Main Tray + 100-sheet Multi-Purpose Tray); 2,540 sheets Max (with Optional 535-sheet 2nd, 3rd, 4th & 5th Trays)

#### **PAPER SIZES**

A3, A4, A5, A6, B4, B5, B6, B6 Half, Legal 13, Legal 13.5, Legal 14, Tabloid (11" x 17"), Letter, Executive, 16K, 8K, Statement, Folio, Banner, Envelopes, Postcard, Return postcard, Index Card (3" x 5") (75 x 125mm), Photo Size (4" x 6", 5" x 7") (100 x . 150mm, 125 x 175mm), Custom Size: Width 2.2-11.7" (55-297mm) x Length 3.5-52" (90-1,321mm), B7, B8

#### **PAPER WEIGHT**

Main Tray / Duplex	64 to 220gsm;
Multi-Purpose Tray	64 to 256gsm;
Optional Tray	64 to 176gsm;

**PAPER OUTPUT** 

Main Output Bin: 250 sheets (80gsm); Face up tray: 100 sheets (80gsm)

#### **DUPLEX (2-SIDED PRINTING)**

Standard

#### **ENVIRONMENT (TEMPERATURE/HUMIDITY)**

50°F to 90°F (10°C to 32°C ), 20% to 80% RH

14°F to 109°F (-10°C to 43°C), 10% to 90% RH

Operating Storage

#### **POWER SUPPLY**

Single phase 120VAC or 220-240VAC, frequency 50/60 Hz +/- 2%







