



MIP480

Ideally suited to
route delivery



HIGHLIGHTS AT A GLANCE:

- Fastest impact mobile printer available today for truck use
- Rugged construction
- Simple to change ribbon
- Comprehensive set of interfaces:
- Parallel, Serial RS232, USB-2 and Bluetooth
- Easy paper loading
- 12-24 volts nominal for compatibility with a wide range of trucks
- Wide range of accessories

MIP480

The MIP480 is an impact printer, designed primarily for delivery note printing in commercial vans and trucks. It is ideally suited for truck operation where it can be powered from the vehicle's battery.

It can print up to 480 characters per second (400 cps at 10 characters per inch) and its 24-wire print head produces exceedingly clear text and graphic output on up to 4-part continuous and single sheet forms.

TECHNICAL SPECIFICATIONS

Print Speed	600 cps (Fastest Draft); 400 cps (Draft), 133 cps (LQ) at 10 cpi
Resolution	up to 180 x 360 dpi
Throughput (ECMA 132)	321 pages per hour
Character Density	10, 12, 15, 17.1, 20, 24 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Print head Life	300 million strokes
Memory	64 kB
Standard Connectivity	Parallel (Bi-directional), Serial RS-232, USB 2.0 and Bluetooth 1.2
Standard Emulation	IBM ProPrinter XL24E, Epson ESC P/2, Intermec 6820
Fonts	Draft, Courier, Roman, Sans Serif, Bold, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 9 Barcodes
Consumables	Ribbon: 4 million characters
Standard Paper Handling	Push tractor and friction
Number of Copies	1 original + 3 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60 - 260 g/m ²
Paper Size	Width: 102 to 267 mm Length: 76 to 365 (cut sheet) Width: 102 to 267 mm (Continuous forms)
Physical Weight	6,2 kg
Physical Size	365 x 263 x 140 mm (W x D x H)
Acoustic	57 dB(A)
Power Voltage	12 -24 V DC for connection in vehicles; 100 - 240 V - 50/60 Hz for stationary usage
Power Consumption	150 W Printing; 7 Watt Stand-By, 2 Watt Sleep Mode, 0,3 W Power Off
Temperature	-20° to +60° C; 30% to 80% humidity (Printing) -30° to +65° C; 30% to 90% humidity (Storing)
Workload	20.000 pages per month
MTBF	15.000 hours
Drivers	Windows 8/8.1/10 and Server 2012/2016/2019; Android App
Approvals	CE C22.2 Nr. 950, EN 60950, GS, UL, E-Mark, ASTM

Configuration:

- MIP480 Standard model

DASCOM GB Ltd
Hart House, Priestley Road
Basingstoke | Hampshire RG24 9PU | ENGLAND
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400
info.gb@dascom-com | www.dascom.co.uk

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047